

## FasNSeal® UNIVERSAL CONDENSATE DRAIN

Designed to drain vertical as well as horizontal vent systems, the Universal Condensate Drain is manufactured from AL29-4C stainless steel with a built-in mechanical locking band and gasket. The Universal Condensate Drain allows one drain product to be positioned anywhere in the system making it possible to vent without a horizontal transition.

- Collects side wall condensate in the horizontal and vertical orientations
- Mates to any of our standard FasNSeal® vent lengths
- Less pressure drop than an Elbow, Drain fitting Tee combination
- Accepts 1/2" - 5/8" ID flexible tubing

FasNSeal® Universal Condensate Drain				
A	B	C		
Vent Diameter	Effective Length	Overall Length	Product Number	Part Number
4	6.31	8.4	300960	FSUCD4
5	6.31	8.4	300961	FSUCD5
6	6.31	8.4	300962	FSUCD6
7	6.31	8.4	300963	FSUCD7
8	6.31	8.4	300964	FSUCD8
9	6.31	8.4	300965	FSUCD9
10	6.31	8.4	300966	FSUCD10
12	6.31	8.4	300967	FSUCD12
14	6.31	8.4	300968	FSUCD14
16	6.31	8.4	300969	FSUCD16

Refer to the FasNSeal® Installation Instructions (Literature No. 1150B) for proper installation techniques.

Note: Not recommended for use in the vertical mode for vertical terminations without a rain cap

**WARNING:** Risk of Flue Gas Leak. The use of an Adjustable Vent Length is **NOT RECOMMENDED** at the top of the Universal Condensate Drain. If an Adjustable Vent Length is used you must have a minimum of 2" of insertion, the **MAXIMUM MUST NEVER** exceed 4" as you will block the hose fitting which will prevent the drain from operating.

